

MLL I Single Magazine Line Loader



AUTOMATION



- Compact, Reliable PCB Line Loader
- Ideal for Fast Running Lines
- Expandable with Magazine Changer
- Lean Design - Optimized Footprint
- User Friendly Interface - LCD Touchscreen
- Easy Configuration
- Integrated Diagnostic Tool
- Welded Steel Frame



EXPERTS IN FACTORY AUTOMATION

MLL I

Single Magazine Line Loader

PCB Specification (based on standard magazine type CAB 703)	
PCB Width:	50 - 310 mm (1.97 - 12.20")
PCB Length:	50 - 387 mm (1.97 - 15.23")
PCB Thickness:	0.5 - 4 mm (0.02 - 0.15")
Height of Components (Top Side):	max. 100 mm (3.9")
Height of Components (Bottom Side):	max. 25 mm (1.0")
PCB Weight:	2.5 kg
Technical Specification	
Standard Magazine Type:	CAB 703
Lift Velocity:	5 and 150 mm/s (0.2 and 5.9"/s)
Lift Height Positioning:	±0.3 mm (0.01")
Fix Side Accuracy:	±0.1 mm (0.004")
Pitch	10 mm (0.4") programmable
PCB Exchange Time:	6 sec
PCB Edge Support:	2.5 - 5 mm (0.1 - 0.2")
Transport Height:	920 ± 50 mm (36.2 ± 1.9 ")
Transport Direction:	L -> R, R -> L (to be specified at time of order)
Energy Requirements:	230 ± 10%, 50Hz - 110V ± 10%, 60 Hz - 400 VA
Compressed Air:	5-7 bar, 40 l/min, according to DIN ISO 8573 3.4.5
Color:	RAL 7035
Dimensions (L x D x H):	1,300 x 690 x 1,840 mm (51.2 x 27.2 x 72.4")
Weight:	225 kg
Control Unit:	Omron
Standards:	CE Approved
Interface:	SMEMA
Options	
Automatic Width Adjustment	
Bus System	RS 232 / RS 485, Ethernet
SMEMA Specific	Siemens, SMPI, Fuji, Panasonic, Sanyo
Other Magazine types	Mikiplastic



■ IPTE N.V.

Geleenlaan 5
3600 Genk
Belgium
Tel.: +32 (0)89 623 000
Fax.: +32 (0)89 623 010
email: info@ipte.com

■ IPTE SALES

Detailed information on our worldwide sales offices can be found on our website at www.ipte.com