

FLU Flip Unit



AUTOMATION



- Smooth PCB Flipping
- Lean Design - Optimized Footprint
- User Friendly Interface – LCD Touchscreen
- Easy Configuration
- Integrated Diagnostic Tool
- Welded Steel Frame



EXPERTS IN FACTORY AUTOMATION

FLU Flip Unit

PCB Specification	
PCB Width:	50 - 360 mm (1.97 - 14.17")
PCB Length:	50 - 460 mm (1.97 - 18.11")
PCB Thickness:	0.5 - 4 mm (0.02 - 0.15")
Height of Components (Top Side):	50 mm (2.0")
Height of Components (Bottom Side):	50 mm (2.0")
PCB Weight:	2.5 kg
Technical Specification	
Cycle Time:	8 sec
PCB Edge Support:	2.5 - 5 mm (0.1 - 0.2")
PCB Transport Speed:	100 to 800 mm/sec (3.9 - 31.5"/sec)
Transport Height:	920 ± 50 mm (36.2 ± 1.9 ")
Transport Direction:	L -> R
Energy Requirements:	230 ± 10%, 50Hz - 110V ± 10%, 60 Hz
Compressed Air:	5-7 bar, 40 l/min, according to DIN ISO 8573 3.4.5
Color:	RAL 7035
Dimensions (L x D x H):	500 x 760 x 1,300 mm (19.7 x 29.9 x 51.1")
Weight:	115 kg
Control Unit:	Omron
Standards:	CE Approved
Interface:	SMEMA
Options	
Automatic Width Adjustment	
Bus System	RS 232 / RS 485, Ethernet
SMEMA Specific	Siemens, SMPI, Fuji, Panasonic, Sanyo
Transport height	



■ IPTE N.V.
 Geleenlaan 5
 3600 Genk
 Belgium
 Tel.: +32 (0)89 623 000
 Fax.: +32 (0)89 623 010
 email: info@ipte.com

■ IPTE SALES
 Detailed information on our
 worldwide sales offices can
 be found on our website at
www.ipte.com