

ETH EasyTest Handler

TEST



- Automatic In-Line Test and Programming
- Optional Pass-Through in Contacting Position
- Economical Fixture
- Single and Dual Side Contacting
- Optimized Footprint
- Multifunctional Test Handling
- 19" Mounting Space
- Easy Fixture Exchange

OPTTE
EXPERTS IN FACTORY AUTOMATION

ETH EasyTest Handler

Technical Specification	
PCB Width:	40 - 350 mm (1.6 - 13.8")
PCB Length:	50 - 400 mm (2 - 15.7")
PCB Ratio:	0.8 (Length >= 0.8 Width)
PCB Thickness:	> 0.4 mm (0.015")
Top Side Clearance:	Max. 50.8 mm (2.0")
Bottom Side Clearance:	Max. 25.4 mm (1")
PCB Edge Support:	2.5 - 5 mm (0.1 - 0.2") adjustable
Product Weight:	Max. 2.5 kg (5.5 lbs)
Transport Direction:	L -> R, R -> L software selectable
Transport Speed:	100 - 800 mm/sec (4 - 31.5"/sec)
Transport Height:	920 ± 50 mm (36.2" + 2")
PCB Exchange Time:	typical 4 seconds for PCB, 1.5 seconds for bypass
Fixture Exchange Time:	< 1 min
Fixture Weight:	upper 5 kg, lower 5 kg (depending on application)
Drive Force:	750 N (pneumatical)
Protection Screens:	ESD Safe
Energy Requirements:	90 - 265 V AC, 50/60 Hz, 120 VA
Compressed Air:	6 bar - 20%, according to DIN ISO 8573 3.4.5
Color:	RAL 7035
Dimensions (L x D x H):	500 x 820 x 1,500 mm (19.7 x 32.3 x 59.0") excluding light tower
Weight:	ca 250 kg (550 lbs)
Stopper:	Standard on Transport Rail
Control:	Omron PLC with LCD Operator Panel
Interface to Test PC:	interface DLL to be installed on Test PC
Standards:	SMEMA, CE Approved
Options	
Bypass Conveyor	
Stopper and Sensors in Fixture	



■ IPTE N.V.

Geleenlaan 5
3600 Genk
Belgium
Tel.: +32 (0)89 623 000
Fax.: +32 (0)89 623 010
email: info@ipte.com

■ IPTE SALES

Detailed information on our worldwide sales offices can be found on our website at www.ipite.com